

Delo[®] 400 XSP-SD SAE 5W-30

High performance synthetic heavy-duty diesel engine oil

Product description

Delo 400 XSP-SD 5W-30 is a high performance synthetic heavy-duty diesel and gas engine oil formulated for fuel economy and extended drain, and meets the performance requirements of many naturally aspirated and turbocharged engines in on-highway, off-highway and construction service.

Delo 400 XSP-SD SAE 5W-30 is based on ISOSYN[®] technology, which uses low SAPS additive design to meet Euro VI emission requirements.

Delo 400 XSP-SD SAE 5W-30 is formulated with advanced dispersant and detergent technologies, and offers optimum wear, corrosion and oxidation protection with foam suppression, and viscosity improvers.



Product highlights

- **Designed for improved fuel economy**
- **Offers extended drain wear protection**
- **Designed for cold-start protection**
- **Formulated for keep-clean performance**
- **Helps minimise DPF cleaning**
- **Offers wear, oxidation and sludge control**

Selected specification standards include:

ACEA	API
Caterpillar	Cummins
Detroit Diesel	Deutz
JASO	Mack
Mercedes Benz	MTU
Renault Trucks	Volvo

Customer benefits

- Designed to provide improved fuel economy, high performance extended drain engine wear protection and optimum engine service life
- Low viscosity synthetic base oil promotes cold engine start wear protection for engines operating in sub-zero temperatures
- Formulated for soot dispersancy and wear control, helping to keep piston rings, valve and piston lands clean, improving uptime
- Helps minimise Diesel Particulate Filter (DPF) emission control system cleaning, and offers improved service life
- Advanced synthetic base stocks and additives offer extended drain through wear, oxidation, sludge and oil thickening control

Applications

- Delo 400 XSP-SD SAE 5W-30 is formulated for four-stroke naturally aspirated and turbocharged diesel engines and is recommended for engines meeting Euro I - Euro V and the newest Euro VI emissions requirements, where allowed by OEMs. It is suitable for use with many after treatment systems.
- Delo 400 XSP-SD SAE 5W-30 is recommended for use in older engines as well as today's modern low emission designs. It is formulated for high performance with many fuels including low sulphur and ultra-low sulphur diesel fuels, and many biofuel formulations.

Approvals, performance and recommendations

Approvals

- Cummins CES 20086
- Detroit Diesel DFS 93K222
- Deutz DQC IV-18 LA
DQC TTCD^o
- Mack EOS-4.5
- Mercedes Benz MB-Approval 228.51
- MTU Oil Category 3.1
- Renault Trucks RLD-3
- Volvo VDS-4.5

Performance

- ACEA E6, E7, E9
- API CK-4, CJ-4, CI-4 Plus, CI-4, CH-4
SN, SM, SL, SJ
- JASO DH-2
- Caterpillar ECF-3
- DAF Extended drain (Euro IV to VI)*
- Mack EO-O Premium Plus, EO-N,
EO-M Plus, EO-M
- Renault Trucks RLD-2, RLD, RXD, RGD
- Volvo VDS-4, VDS-3

Suitable for use

Delo 400 XSP-SD SAE 5W-30 is suitable for use in applications requiring:

- Ford WSS-M2C213-A1
- Renault Trucks RD-2, RD
- Volvo VDS-2, VDS

^o Product approved for DQC IV-18 LA are also approved for use in Deutz TTCD engines

* Can be used in Euro IV & Euro V MX engines and in Euro VI MX & PX engines for DAF.

Typical test data		
Test	Test Methods	Results
Viscosity Grade		5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.858
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	71.5
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	11.9
Viscosity Index	ASTM D2270	164
Pour point, °C	ASTM D97	-39
Flash point COC, °C	ASTM D92	231
Total Base Number, mg KOH/g	ASTM D2896	9.5
Sulphated Ash, %wt	ASTM D874	1.0

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product